



Screen Vision SV 3% (hors collection)


filtersun




0101




0102




0110




SV3-0202 (00020002)




SV3-0207 (00020007)




0210




SV3-0220 (00020004)




SV3-0701 (00070001)




SV3-0707 (00070007)




SV3-0720 (00070004)




SV3-3001 (00030001)



SV3-3006 (00030006)



SV3-3071 (00030009)

















SV3-3030 (00030003)


Rouleau intérieur
Tarif 5 - Plus value : 58.43 € / m²



Poids (en g/m²)	385
Épaisseur (en mm)	0.48
Coeff. ouverture (en %)	3.00
Composition	36 % Fibre de verre - 64 % PVC
Soudable	Oui
Entretien	Épongeable
Sens d'enroulement	Vertical et horizontal
Largeur de laize (mm)	2500

Recto	Réf. rouleaux	Transmission solaire	Réflexion solaire	Absorption solaire	gtot	Transmission lumière visible
	0101	9 %	20 %	71 %	0,28	5 %
	0102	10 %	30 %	60 %	0,25	7 %
	0110	8 %	23 %	69 %	0,28	4 %
	SV3-0202 (00020002)	21 %	66 %	13 %	0,13	0,20
	SV3-0207 (00020007)	18 %	57 %	25 %	0,15	0,16
	0210	16 %	57 %	27 %	0,17	13 %
	SV3-0220 (00020004)	20 %	62 %	18 %	0,14	0,18
	SV3-0701 (00070001)	12 %	32 %	56 %	0,24	0,09
	SV3-0707 (00070007)	14 %	36 %	50 %	0,22	0,12

Recto	Réf. rouleaux	Transmission solaire	Réflexion solaire	Absorption solaire	gtot	Transmission lumière visible
	SV3-0720 (00070004)	16 %	40 %	44 %	0,21	0,13
	SV3-3001 (00030001)	4 %	8 %	88 %	0,30	0,04
	SV3-3006 (00030006)	4 %	6 %	90 %	0,31	0,04
	SV3-3071 (00030009)	4 %	11 %	85 %	0,29	0,04
	SV3-3030 (00030003)	3 %	5 %	92 %	0,31	0,03