


Vénitiens Alu 50 mm Cat. 3


filtersun




1510




4495




7903




8010



8150




8192




8221



8222




8223




8224




8232




8233




8236



8258




8259




8262




8698



8725



8858



9771



Autre
 Tarif 3 - Plus value : 20.00 € / m²



Intérieur

Coeff. ouverture (en %)








0.00










Composition





Aluminium

Soudable

-

Recto	Réf.	Transmission solaire	Réflexion solaire	gtot	Transmission lumière visible
	1510	0 %	9,1 %	0,52	0 %
	4495	0 %	67,1 %	0,35	0 %
	7903	0 %	47,5 %	0,41	0 %
	8010	7,9 %	44,6 %	0,41	7,9 %
	8150	7,9 %	64,7 %	0,35	7,9 %
	8192	0 %	71,8 %	0,33	0 %
	8221				

Recto	Réf.	Transmission solaire	Réflexion solaire	g _{tot}	Transmission lumière visible
	8222				
	8223				
	8224				
	8232				
	8233				
	8236				
	8258	0 %	6,7 %	0,55	0 %
	8259	0 %	33,8 %	0,46	0 %
	8262				

Recto	Réf.	Transmission solaire	Réflexion solaire	g _{tot}	Transmission lumière visible
	8698	0 %	38,4 %	0,43	0 %
	8725				
	8858	7,9 %	4,8 %	0,54	7,9 %
	9771	0 %	19,6 %	0,49	0 %