


Vénitiens Alu Classic Cat. 3


filtersun




4495




7327




8010




8150




8192




8204




8221




8224



8236




8258




8459



8698



8858



8952



9771



Autre
Tarif 3



Intérieur

Épaisseur (en mm)








0.22

Composition

Aluminium

Soudable

-

Recto	Réf.	Transmission solaire	Réflexion solaire	gtot	Transmission lumière visible
	4495	0 %	67,1 %	0,35	0 %
	7327	0 %	60,6 %	0,37	0 %
	8010	7.9 %	44.6 %	0,41	7,9 %
	8150	7.9 %	64.7 %	0,35	7,9 %
	8192	0 %	71.8 %	0,33	0 %
	8204	7.9 %	62.9 %	0,36	7,9 %
	8221				

Recto	Réf.	Transmission solaire	Réflexion solaire	g _{tot}	Transmission lumière visible
	8224				
	8236				
	8258	0 %	6,7 %	0,55	0 %
	8459	7.9 %	61 %	0,37	7,9 %
	8698	0 %	38,5 %	0,43	0 %
	8858	0 %	4.8 %	0,54	7,9 %
	8952	7.9 %	38.2 %	0,44	7,9 %
	9771	0 %	19.6 %	0,49	0 %